High end small flatbed UV printer

for customizing graphics on various substrates!



H0906E|

-high resolution, high speed and high durability Epson I3200 print heads!






Epson I3200 U1 Print Heads




4 water-cooling LED UV lamps



Precise vacuum platen with 12 adjustable points



Anti-collisionunit protects print heads




75 cm width front clyinder printing kit



Auto-matic media detector for up to 150mm thick media

Much higher productivity than H0906TX!



* The time is shorter, the printing speed is faster.







ITEM	SPECIFICATION				
Model	H0906EI				
Print Head	2~3 Epson I3200 U1 print heads				
Print Technology	Drop-On-Demand Piezo with Variable Dot				
Resolution	720x1200dpi~720x1800dpi				
Curing System	Four water cooling LED UV curing lamps				
Ink	UV curable ink				
Color Configuration	CMYK; CMYK+W; CMYK+W+V				
Ink Supply System	Bulk ink supply system with white ink stirring unit				
Ink Tank	500ml				
Media Thickness	Up to150mm				
Media Type	Acrylic, Aluminum sheet, Foam board, PVC board, Leather, Glass bottle, Wood, Ceramic tile, etc				
Printing Size	Max. 900x600mm				
Printing Speed	Printing mode	Resolution	Feather	CMYK+W	CMYK+W+V
	Draft Production Hi-resolution Photo	720x1200dpi 720x1200dpi 720x1800dpi 720x1800dpi	Weak Medium Weak Medium	4.2mins/sheet 5.0mins/sheet 6.3mins/sheet 7.5mins/sheet	4.5mins/sheet 5.5mins/sheet 6.8mins/sheet 8.3mins/sheet
Data Interface	Gigabit Ethernet				
Working Environment	Temp.20°C~30°C, Humidity:35%~65%				
Software	FlexiPRINT Mini UV+GZ control console				
Power Requirements	Single-phase, AC220V±10%, 50/60Hz, 10A				
Power Consumption	Printer: Approx. 1100W; UV controller: Approx. 800W				
Installation/Package Dimension	LxWxH(mm): 2180x1565x1371/2300x1770x1600				
N.W./G.W.	492kgs/690kgs				
*Specifications are liable to change without prior n	otice. 1 sheet is 90X60c	m.			









🦠 โทรศัพท์ : 09–1031–7494 ติดต่อบริษัท 🛮 🜭 โทรศัพท์ : 0–2045–6513 โทรและแฟกซ์