

踏上变革之路 体验中国速度



彩旗条幅一体机 NSPL-160X SUBLIMATION BANNER PRINTER



喷头加热系统

不管天气变化，喷头恒温打印，保证不断墨。

Print-head Heating System:

Printing smoothly with the print-heads working under the constant temperature.



墨盒加热系统

二级墨盒带加热，墨水更流畅。

Ink Tank Heating System:

Preheat the ink in the sub tanks, for the ink get into the print-heads smoothly.



THK 静音导轨

THK sound off guideway.



自动分切系统

节省裁布时间，工作效率大幅提高。

Auto Media Cutting System:

Saving the time of manual cutting to improve the working efficiency.

内容 Item		规格 Specification			
型号 Model		NSPL-160X			
喷头 Printhead		KONICA 512i (13PL)		KONICA 512 (35PL)	
喷头数量 Number of Printhead		4	2	8	4
打印宽度 Maximum Print Width		1.6M(63inch)			
打印颜色 Color		CMYK 彩色	Red 单色(大红)	CMYK 彩色	
打印速度 Print Speed	草稿模式 Draft	90 m ² /hr	180 m ² /hr	210 m ² /hr	110 m ² /hr
	标准模式 Standard	65 m ² /hr	130 m ² /hr	175 m ² /hr	60 m ² /hr
	精细模式 Ultra	50 m ² /hr	100 m ² /hr	95 m ² /hr	45 m ² /hr
介质 Media		Sublimation Fabric 热升华专用布			
最高打印精度 Maximum Print quality		1440dpi		720dpi	
自动放布系统 Auto Media System		标配 Equipped			
喷头自动清洗系统 Auto Cleaning System		正压清洗 Positive Pressure Cleaning 防堵闪喷功能 Spray in Idel Function			
图像格式 Image Format		Bitmap, TIFF, Quark Xpress, JPEG, AI, EPS, PDF			
色彩管理 Color Management		国际ICC曲线 Superior ICC Profile			
工作流程 Work Flow		先RIP后打印或者是边RIP边打印 RIP and Print at the same time/Print after RIP			
数据传输接口 Print Interface		USB2.0			
墨水类型 Ink Type		Sublimation Ink 热升华专用墨水			
软件 Software		Photo Print , Revotech Edition			
机器尺寸 (长*宽*高) Machine Dimension		270 X 94 X 173 CM			